

ROBUS®

DOWNLIGHTS

ULTIMUM EXPRESS LED FIRE RATED DOWNLIGHT

5W/7W, IP65



PRODUCT INFORMATION DOCUMENT

FEATURES

- Unique wattage selectable design with choices of 5W and 7W via switch located on the back of the fitting
- Colour temperature selectable; switch on the front of the fitting allows selection between 2700/3000/4000/6000K
- Market leading quick release 2 part connector with high quality colour coded lever terminals makes installation fast and secure
- Tested in compliance with EN 1365-2 Fire resistance tests for loadbearing elements & EN 1363-1 Fire Resistance tests Part1: General Requirements
- Fire Tested for use in 30min/60min/90min Solid Timber Joists
- Tested for use with I-Joists & Metal Web Joists

CONSTRUCTION

- Polycarbonate trim and LEDchroic lens optic
- Die-cast aluminium heatsink
- Pressed steel and polycarbonate body
- Spring steel ceiling fixing springs with PVC protectors



WARRANTY



LIFETIME



LUMENS PER W



FIRED RATED



IP RATING



OPERATING VOLTAGE



BEAM ANGLE



DIMMING



CCT



SAFETY CLASS

Product Code:	RULT06X4-01
Comparable to:	50W halogen
Total Power (W):	5.2/6.6
Power Factor:	0.9
Total Light Output (lm):	660/820
Emergency Light Output (lm):	NA
Efficacy (lm/cctW):	130/125
Lux at 1m (lux):	540/670
Emergency Lux at 1m (lux):	NA
CCT (K):	2700/3000/4000/5700
CRI:	80
IP:	65
Operation Temperature (°C):	-20 ≤ Ta ≤ +40
Inrush Current:	7.5A/100us
RG Value:	0
SDCM:	6
Pst LM:	NA
SVM:	NA
Energy Class:	D
Rated Life to L70B50 (Hrs):	30000
Dimensions ØxH (mm):	85x56
Cut Out (mm):	72
Weight (kg):	0.32
Separate Control Gear Information	
Type of Light Source:	LED
Full Load Efficiency (%):	84
P _{NET} (W):	NA
Dimensions (mm):	48x40x17

Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances.

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
UK: TEL: 0800 973 220
AUS: TEL: +61 7 3890 5444
NZ: TEL: +64 03 668 5285

WEB: ROB.US.COM
WEB: ROB.US.COM
WEB: ROB.US.COM.AU
WEB: ROB.USLED.CO.NZ

LED GROUP EUROPE · UK · AUSTRALIA · NEW ZEALAND · ASIA · MIDDLE EAST · AFRICA

ULTIMUM EXPRESS LED FIRE RATED DOWNLIGHT 5W/7W, IP65

Cone Illuminance Diagram




Diagram for RULX-01 in 7W, 4000K. Other diagrams available on request

Polar Intensity Diagram





Diagram for RULX-01 in 7W, 4000K. Other diagrams available on request

Dimension Diagram



Sensor Data

Time Off Delay:	NA
Illuminance Switching Range:	NA
Sensitivity Range (%):	NA
Mounting Height (max):	NA
Detection Zone Diameter (max):	NA

Accessories

RULSTRIM-03	ULTIMUM+ trim, Polished Chrome
RULSTRIM-10	ULTIMUM+ trim, Matte Black
RULSTRIM-13	ULTIMUM+ trim, Brushed Chrome
RULSTRIM-14	ULTIMUM+ trim, Antique Brass
RLA250DTG-01	LOADPRO 250W LED Grid Dimmer
R1001G2W	100W LED Wall Plate Dimmer